



NOTE

- CONTACT PLATING
GOLD (0.2 μm MIN.) ON MATING AREA,
GOLD (0.05 μm MIN.) ON TERMINATION AREA,
ALL OVER NICKEL UNDERPLATED.
- MATING CONNECTOR
P/N: PCS- (NO. OF POS.) MD () +
- STACKING HEIGHT: 15.0mm (.591)

PART NO.	NO. OF POS.	A	B	C	POS. NO.	PART NO.
PCS-150FD+	150	105.29 (4.145)	1.27x (75-1) = 93.98 (.05) (3.700)	98.15 (3.864)	1, 75, 76, 150	HONDA PCS-150FD JAPAN
PCS-96FD+	96	71.0 (2.795)	1.27x (48-1) = 59.69 (.05) (2.350)	63.86 (2.514)	1, 48, 49, 96	HONDA PCS-96FD
PCS-68FD+	68	53.22 (2.095)	1.27x (34-1) = 41.91 (.05) (1.650)	46.08 (1.814)	1, 34, 35, 68	HONDA PCS-68FD
PCS-48FD+	48	40.52 (1.595)	1.27x (24-1) = 29.21 (.05) (1.150)	33.38 (1.314)	1, 24, 25, 48	HONDA PCS-48FD
PCS-34FD+	34	31.63 (1.245)	1.27x (17-1) = 20.32 (.05) (.800)	24.49 (.964)	1, 17, 18, 34	HONDA PCS-34FD

REV.	DATE	BY	REV. DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
3									
2					CONTACT	PHOSPHOR BRONZE			NOTE #1
1					INSULATOR	PBT (GF)			UL94V-0 BLACK

DATE	SCALE	UNIT	3RD. A. P	NAME	PART NO.	REV.
APR. 16 (2004)	2/1	mm (INCH)	3RD. A. P	本多通信工業株式会社 HONDA TSUSHIN KOGYO CO., LTD.	PCS SERIES FEMALE STACKING CONNECTOR (RoHS)	
T. KAWANO	T. KAWANO	T. SOGO	K. HOMMA	K. SATO	PCS- () FD+	