



PCS-E68LA	68	8.5x7.5	50.6	60.3	Ø8.1
PCS-E50LA	50	8.5x7	39.2	48.9	Ø7.3, Ø8
PCS-E36LA	36	9.5x8	30.5	40.2	Ø8.4, Ø9
PCS-E28LB	28	9.5x8.5	25.3	35.0	Ø9
PCS-E28LA		6.5x5			Ø5.5, Ø5.9
PCS-E20LC	20	10.3x8.5	20.3	30.0	Ø8.7+Ø4.3
PCS-E20LB		8x7			Ø7.5
PCS-E20LA		6x5			Ø5.5
PART NO.	NO. OF POS.	A	B	C	APPLICABLE CABLE O. D.
DIMENSIONS					

HONDA TSUSHIN KOGYO CO., LTD.
 This product information in this data is for reference only.
 This is subject to change without notice.
 Contact our sales staff for further information before considering or ordering any of our products.
 Please request the Engineering Drawing for the most current and accurate design information.

△				6	FLAT HEAD SCREW	STEEL	2	NICKEL PLATING	M2.5	
△				5	COVER A	ZINC ALLOY	1	NICKEL PLATING	—	
△				4	COVER B	ZINC ALLOY	1	NICKEL PLATING	—	
△				3	SPRING LOCK	STAINLESS STEEL	2	—	—	
△				2	PAN HEAD SCREW	STEEL	2	NICKEL PLATING	M2.5	
△				1	CABLE CLAMP	STAINLESS STEEL	1	—	—	
LTR.	DATE	BY	REV.	DESCRIP	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	4. APR. 1997		2 / 1							
DATE					SCALE		UNIT		3RD. A. P	
APP. DATE&REV.					HONDA TSUSHIN KOGYO CO., LTD.					
DR.	DE.	CHK.	CHK.	APP.	NAME		PCS-E TYPE CABLE COVER			
K. YOKOTA	K. YOKOTA	K. SATO	Y. HIRAI	H. MIYAZAKI	PART NO.		PCS-E () L ()			