



CONTACT DETAIL

- 1. CONTACT PLATING
 MATING AREA: 0.76 MICRO METERS MINIMUM GOLD PLATING
 TERMINATION AREA: 0.05 MICRO METERS MINIMUM GOLD PLATING
 UNDERPLATING: NICKEL PLATING
- 2. APPLICABLE HOOD
 HDR-26LPH ()
- 3. MATING CONNECTOR
 HDR-EA26LMY () G1+
 HDR-E26M () G1+
- 4. SPECIFICATION
 RATED CURRENT 0.5A
 RATED VOLTAGE 125V AC (r. m. s.)

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE	
					4	SPACER	PA9T (GF)	1	—	UL94V-0 BLACK	
					3	INSULATOR	PA9T (GF)	1	—	UL94V-0 BLACK	
					2	SHELL	STEEL	1	NICKEL PLATING	—	
					1	FEMALE CONTACT	PHOSPHOR BRONZE	26	NOTE#1	—	
DATE					SCALE	UNIT	3RD. A. P				
Feb. 22, 2007					3 / 1	mm (INCH)	HONDA TSUSHIN KOGYO CO., LTD.				
APP. DATE&REV.					DR.	DE.	CHK.	CHK.	APP.	NAME	0.8mm SPACING SHIELDED FEMALE CABLE CONNECTOR (RoHS)
					Y. KATO	Y. KATO	—	C. NUNOKAWA	H. EBIHARA	PART NO.	HDR-E26FSG1+
										REV.	