



- 1. CONTACT PLATING
MATING AREA: 0.76 MICROMETERS MINIMUM GOLD PLATING
TERMINATION AREA: 0.05 MICROMETERS MINIMUM GOLD PLATING
UNDERPLATING: NICKEL PLATING
- 2. APPLICABLE HOOD
HDR-26LPH ()

- 3. MATING CONNECTOR
HDR-EA26LFY () G1+
HDR-E26LFY () G1+
HDR-EC26LFDT () +
- 4. SPECIFICATION
RATED CURRENT 0.5A
RATED VOLTAGE 125V AC (r. m. s.)

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
△3	Apr. 23 2007	Y. K		SHAPE (SPACER)	4	SPACER	PA9T (GF)	1	—	UL94V-0 BLACK
△2	MAR. 17 2006	M. M		REVISE	3	INSULATOR	PBT (GF)△1	1	—	UL94V-0 BLACK
△1	JUN. 19 2005	M. M		CHANGE MATERIAL AND FORM	2	SHELL	STEEL	1	NICKEL PLATING	—
					1	MALE CONTACT	PHOSPHOR BRONZE	26	NOTE#1	—

DATE	SCALE	UNIT	3RD. A. P			HONDA TSUSHIN KOGYO CO., LTD.				
Oct. 20. 2004	3 / 1	mm (INCH)								
APP. DATE & REV.										
DR.	DE.	CHK.	CHK.	APP.	NAME		0.8mm SPACING SHIELDED MALE CABLE CONNECTOR			
Y. KATO	M. MIYAZAKI	—	C. NUNOKAWA	K. KASHIO	PART NO.		HDR-E26MSG1+△			
										REV. 3C