



DRAWING AFTER CONNECTOR ASSEMBLY

NOTE#1. APPLICABLE CONNECTOR: HDRA-E100M () 1
 #2. APPLICABLE CABLE DIA. : Ø7.3

掲載している製品の仕様及び性能は参考値です。性能及び仕様についてよく変更する場合があります。お問い合わせは、当社担当窓口までお問い合わせをお願いします。
 The product information in this data is for reference only. This is subject to change without notice. Contact our sales staff for further information before ordering or ordering any of our products. Please request engineering drawing for the most recent and accurate design information.

5	LOCK SCREW	STEEL	2	NICKEL PLATING	
4	⊕FLAT HEAD SCREW	STEEL	2		M2.5x0.45 l=8
3	⊕FLAT HEAD SCREW	STEEL	2		M2.5x0.45 l=5
2	COVER B	ZINC ALLOY	1	NICKEL PLATING	
1	COVER A	ZINC ALLOY	1	NICKEL PLATING	

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	OCT.3.2001		2 / 1							
DR.	DE.	CHK.	CHK.	APP.		NAME	HDRA-E TYPE CABLE COVER			
Y. KATO	Y. KATO	—	C. NUNOKAWA	H. EBIHARA		PART NO.	HDRA-E100LPWB			REV.