



NOTE #1.  
CONTACT PLATING

CONTACT AREA: GOLD 0.1 μm MIN.  
OVER PALLADIUM/NICKEL 0.5 μm

TERMINAL AREA: GOLD 0.05 μm  
ALL OVER NICKEL UNDERPLATED.

8	PROTECTIVE COVER	PPS	1		UL94V-0 BLACK
7	SPACER	STEEL	1		
6	BOARD LOCK	PHOSPHOR BRONZE	2	NICKEL PLATING	
5	SQR. NUT	BRASS	4	NICKEL PLATING	M2x0.4
4	SHELL	STEEL	2	NICKEL PLATING	
3	INSULATOR	PPS	1		UL94V-0 BLACK
2	CONTACT	PHOSPHOR BRONZE	136	SEE NOTE #1	
1	BRACKET	PPS	1		UL94V-0

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
	DATE		SCALE		UNIT					
	Dec.16.2004		2 / 1		mm (INCH)					
	APP. DATE&REV.									
	DR.	DE.	CHK.	CHK.	APP.					
	Y. KATO	Y. KATO		C. NUNOKAWA	H. EBIHARA					
						<b>HTK</b> HONDA TSUSHIN KOGYO CO., LTD.				
						NAME	0.8mm SPACING 68POS. R/A DUAL STACKING FEMALE CONNECTOR			
						PART NO.	HDRA-E68W ( ) LFDT1EC+			
						REV.				

PART No.	A	B	COLOR OF BRACKET
HDRA-E68W5LFDT1EC+	2.72	3.6	BLACK
HDRA-E68W2LFDT1EC+	3.4	3.6	BROWN
HDRA-E68W1LFDT1EC+	2.08	2.28	BLACK